

Product type designation

CP 1543-1

COMMUNICATION PROCESSOR CP 1543-1 FOR CONNECTING SIMATIC S7-1500 TO INDUSTRIAL ETHERNET: TCP/IP, ISO, UDP, S7- COMMUNICATION, IP-BROADCAST/ MULTICAST, SECURITY (HARDWARE- IDENTIFICATION, IP/MAC ACCESS LIST, FIREWALL), DIAGNOSIS SNMPV1/V3, DHCP, FTP CLIENT/ SERVER, E-MAIL, IPV4/IPV6, DATA STORAGE ON SD CARD OF CPU, CLOCK SYNCHRONISATION VIA NTP, ACCESS TO WEBSERVER OF CPU; GIGABIT-SS 1XRJ45 (10/100/1000 MBIT)



Transmission rate

Transfer rate

- at the 1st interface

10 ... 1000 Mbit/s

Interfaces

Number of interfaces / acc. to Industrial Ethernet

1

Number of electrical connections

- at the 1st interface / acc. to Industrial Ethernet

1

Type of electrical connection

- at the 1st interface / acc. to Industrial Ethernet

RJ45 port

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage

DC

Supply voltage / 1 / from backplane bus

15 V

Relative symmetrical tolerance / for DC

- at 15 V

3 %

Consumed current

- from backplane bus / for DC / at 15 V / typical

0.35 A

Active power loss

5.3 W

Permitted ambient conditions

Ambient temperature

- for vertical installation / during operation
- for horizontally arranged busbars / during operation
- during storage

0 ... 40 °C

0 ... 60 °C

-40 ... +70 °C

| | |
|--|----------------|
| <ul style="list-style-type: none"> during transport | -40 ... +70 °C |
| Relative humidity / at 25 °C / without condensation / during operation / maximum | 95 % |
| Protection class IP | IP20 |

Design, dimensions and weight

| | |
|---|-------------------------------------|
| Module format | Compact module S7-1500 single width |
| Width | 35 mm |
| Height | 142 mm |
| Depth | 129 mm |
| Net weight | 0.35 kg |
| Mounting type <ul style="list-style-type: none"> S7-1500 rail mounting | Yes |

Product properties, functions, components / general

| | |
|---|----------------------------|
| Number of units <ul style="list-style-type: none"> per CPU / maximum Note | 8 depending on CPU type |
|---|----------------------------|

Performance data / open communication

| | |
|---|--|
| Number of possible connections / for open communication <ul style="list-style-type: none"> by means of T blocks / maximum | 118; depending on the system upper limit |
| Amount of data <ul style="list-style-type: none"> as user data per ISO on TCP connection / for open communication / by means of T blocks / maximum | 65536 byte |
| Number of Multicast stations | 118 |

Performance data / S7 communication

| | |
|---|--|
| Number of possible connections / for S7 communication <ul style="list-style-type: none"> maximum Note | 118 depending on the system upper limit |
|---|--|

Performance data / multi-protocol mode

| | |
|---|-----|
| Number of active connections / with multi-protocol mode | 118 |
|---|-----|

Performance data / IT functions

| | |
|---|--------------------|
| Number of possible connections <ul style="list-style-type: none"> as client / by means of FTP / maximum as server / by means of FTP / maximum as server / by means of HTTP / maximum as e-mail client / maximum | 32 16 4 1 |
| Amount of data / as user data for email / maximum | 64 Kibyte |

Performance data / telecontrol

| | |
|--|---|
| Protocol / is supported | |
| <ul style="list-style-type: none"> • TCP/IP | Yes |
| Product functions / management, configuration | |
| Product function / MIB support | Yes |
| Protocol / is supported | |
| <ul style="list-style-type: none"> • SNMP v1 | Yes |
| <ul style="list-style-type: none"> • DCP | Yes |
| <ul style="list-style-type: none"> • LLDP | No |
| Configuration software | |
| <ul style="list-style-type: none"> • required | STEP 7 Professional V12 (TIA Portal) or higher |
| Identification & maintenance function | |
| <ul style="list-style-type: none"> • I&M0 - device-specific information | Yes |
| <ul style="list-style-type: none"> • I&M1 – higher-level designation/location designation | Yes |
| Product functions / Diagnosis | |
| Product function / Web-based diagnostics | Yes; yes, via S7-1500 CPU |
| Product functions / Security | |
| Firewall version | stateful inspection |
| Product function / with VPN connection | IPSec |
| Type of encryption algorithms / with VPN connection | AES-256, AES-192, AES-128, 3DES-168, DES-56 |
| Type of authentication procedure / with VPN connection | Preshared key (PSK), X.509v3 certificates |
| Type of hashing algorithms / with VPN connection | MD5, SHA-1 |
| Number of possible connections / with VPN connection | 16 |
| Product function | |
| <ul style="list-style-type: none"> • password protection for Web applications | No |
| <ul style="list-style-type: none"> • ACL - IP-based | No |
| <ul style="list-style-type: none"> • ACL - IP-based for PLC/routing | No |
| <ul style="list-style-type: none"> • switch-off of non-required services | Yes |
| <ul style="list-style-type: none"> • Blocking of communication via physical ports | No |
| <ul style="list-style-type: none"> • log file for unauthorized access | Yes |
| Product functions / Time | |
| Product function / SICLOCK support | Yes |
| Product function / pass on time synchronization | Yes |
| Protocol / is supported / NTP | Yes |
| Further Information / Internet Links | |
| Internet-Link | |
| <ul style="list-style-type: none"> • to website: Selector SIMATIC NET SELECTION TOOL | http://www.siemens.com/snst |
| <ul style="list-style-type: none"> • to website: Industrial communication | http://www.siemens.com/simatic-net |

- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<https://mall.industry.siemens.com>

<http://www.siemens.com/automation/net/catalog>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

21.05.2015